








	Wireless Box	Wired Box		Dome		PTZ		Megapixel	
									
IDView Model	<a href="#">IV-103LC-RT</a>	<a href="#">IV-LC-B226</a>	<a href="#">IV-LC-B228H</a>	<a href="#">IV-LC-D231H</a>	<a href="#">IV-LC-D233H</a>	<a href="#">IV-LC-18/26/36PTZDN</a>	<a href="#">IV-LC-D244PTZ</a>	<a href="#">IV-LC-B311MP</a>	<a href="#">IV-LC-D331MP</a>
Type	Wireless Box IP-Camera	Wired Box IP-Camera		Vandal-proof / Fixed Dome	3-axis PoE Vandal Proof IP Dome	18/26/36X Optical /12X Digital Zoom	10X Optical/12X Digital Zoom	1.3 Megapixel & WDR IP Camera	
Compression	MJPEG/MPEG4		MJPEG/H.264	MJPEG/MPEG4	MJPEG: 30(25)	MJPEG / MPEG4			
Image sensor	1/4" Sony progressive VGA CCD	1/3" Sony Super HAD CCD (HQ1 DSP)		1/3" Sony CCD	1/3" Sony Super HAD CCD	1/4" Sony CCD	1/4" Sony Exview CCD	1.3 M Sony CMOS Sensor	
Horizontal TV lines	400 TVLs	520 TVLs			520 TV lines				
Min Lux	1.5 lux @F1.2	0.5 lux @F1.2				0.1 Lux@ F1.6	0.1 Lux @ F1.8	0.2 Lux @ F1.2	
Lens type	C/CS-mount			3.6mm	3.3~12mm	3.4~122.4mm	4.2~42mm	not included	3.3~12mm
Auto iris supported	DC-iris			--	YES				
Day & Night	--	--	--	--		YES	--	YES	
Mechanical IR Cut	--	--	--	--				YES	
Max. Image resolution	VGA	720x480 NTSC				4/2/1CIF		1280x960	
Max. Frame Rate	Up to 12 fps at VGA	Up to 30(25) to any resolution	30(25)fps for all resolutions		30(25) FPS at all resolutions,	MJPEG:30(25) MPEG4:30(25)		30 fps in all resolution	
Motion Detection	Advanced MD(zone, position, sensitivity)		Advanced MD( 96 zones & 5 levels selectable)		96 zones, 5 levels			Advanced MD (96 Zones, 5 Level)	
Pan/Tilt/Zoom Control (Adjustmetn angle)	Digital PTZ			Pan: 0~360 Tilting: 0~180		Pan range: 0~360° / Tilt range: 0~180°	Pan range: 0~360° / Tilt range: 0~90°	ePTZ	
Audio	Build-in Mic. One way		two way	--	one way				2 way audio
Network Ethernet	802.11 b WLAN	10/100BaseT Ethernet							
Network Protocols	TCP/IP, DHCP, HTTP, ICMP, UPnP, ARP, DNS, DynDns, PPPoE, *FTP, *SMTP, RTP, RTSP, RTCP								
Alarm I/O	1/1				4/1			1/1	
Analog Video output	1 BNC							1	
SD card supported	YES				SD			SD/SDHC	
Software supported	Free bundle recording software / SDK / ActiveX, also supports Milestone, ONSS, Exaquisition, Saliant								
Temperature	-10 – 50°C	-10 – 50°C	-10 – 50°C	-10 – 50°C	0 – 50°C	-10 – 50°C		0 – 50°C	
Humidity									
Power Requirement	PoE	--	--	--	--	YES	--	--	YES
	DC12V	--	--	YES			--	--	YES
	AC24V	--	--	--	--	YES			
	DC5V	YES		--	--				--
Power Supply Provided	Yes	Yes	Yes						
Dealer Unit Price (USD)	\$262	\$203	\$230	\$246	\$427	\$1586/\$1669/\$1796	\$1,464	\$359	\$503