









	PTZ Camera		Dome Camera			Bullet Camera		Megapixel Camera			
											
IDView Model	IV-SD151VK	IV-SD313VK	IV-FD131VK	IV-FD132VK	IV-FD141VK	IV-IP714VK	IV-IP330VK	IV-FD160VKMP	IV-76MPB	IV-IP361VKMP	
Type	18X PTZ Dome	35X WDR PTZ	Indoor Dome	Indoor Dome	Outdoor Dome	Outdoor Bullet	Outdoor Bullet	Indoor Dome	Megapixel Box	Outdoor Bullet	
Compression	MPEG-4 / MJPEG										
Video Frame Rate	30/25 fps @ 640x480	30/25 fps @ 704 x 480	30/25 fps @ 640 x 480		30/25 fps @ 720 x 480	25 fps @ 720 x 480	30/25 fps @ 640x480	30 fps @ 800x600 up to 10 fps at 1600x1200 MJPEG: up to 30 fps at 800x600			
Image sensor	1/4" SONY Progressive CCD	1/4" Sony Exview HAD CCD	1/4" CMOS sensor		1/3" wide dynamic range CMOS	1/3.3" wide dynamic range CMOS sensor	1/4" CMOS sensor	1/3.2" CMOS sensor	1/3.2" CMOS sensor	1/3.2" CMOS sensor	
Horizontal TV lines	N/A										
Min Lux	1.61/0.38 Lux / F 1.4	0.05/0.01 Lux / F 1.4	1.5 Lux / F1.4	0.56/0 Lux / F1.4	0.68 Lux / F1.4	0.68 Lux / F1.4	0 Lux / F1.8	0.6 Lux / F2.0	0.8 Lux / F1.6	0.1 Lux / 0 Lux F1.2	
Lens type	Varifocal						Fixed	Fixed		Varifocal	
	4.1~73.8 mm	3.4-119 mm	2 ~ 4 mm	3.3 ~ 12 mm	3.3 ~ 12mm	3.3 ~ 12 mm	4.0 mm	2.8mm	4.5 ~ 10 mm	3 ~ 9mm	
Auto iris supported	YES		--	YES	--	--	--	--	--	YES	
Day & Night	YES		--	YES							
Mechanical IR Cut	YES		--	YES			--	--	--	YES	
Max. Image resolution	640x480	704x576	640x480	640x480	720x480	720x480	640x480	800x600	1600x1200	1600x1200	
Max. Frame Rate	Up to 30(25) @		up to 30 fps @ 640x480		up to 25 fps @ 720x480	Up to 25 @ 720x480	Up to 30 @ 640x480	up to 30 fps @ 800x600	up to 30 fps @ 800x600	up to 30 fps @ 800x600	
Motion Detection	YES										
Pan/Tilt/Zoom Control	360°/90°/18X	360°/90°/35X									
Audio	two-way audio							--	two-way audio		
Network Ethernet	10/100 BaseT Ethernet										
Network Protocols	IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE										
Alarm I/O	4/1		one D/I, one D/O				one D/I				one D/I, one D/O
Analog Video output											
SD(CF) card supported	--	SD/SDHC	--	--	SD /SDHC		--			SD /SDHC	
Software supported	Free bundle recording software / SDK NUUO, Milestone, Exacqvision (please call for details)					N/A	N/A	N/A	N/A	N/A	
Temperature	-4°F ~ 140 °F		32 °F ~ 122 °F		-4 °F ~ 122 °F	-4 °F ~ 140 °F	-4 °F ~ 122 °F				
Humidity	20 ~ 80% RH	90% RH	20% ~ 80% RH		20% ~ 95% RH	20% ~ 80% RH	90% RH				
AGC/AWB/AES	YES										
Power Requirement	PoE	--	--	YES							
	DC12V	--	--	YES							
	AC24V	YES		--	--	YES					
	DC5V	--	--	--	--	--	--	--	--	--	
Power Consumption	Max 42 W	Max 45W	Max 3.6W	Max 11W	Max 7.5W	Max 6W	Max 4W	Max 4.3/7.5W	Max 8W	Max 7W	
Dealer Unit Price	\$ 1,496	\$ 2,219	\$ 378	\$ 456	\$ 636	\$ 594	\$ 372	\$ 432	\$ 390	\$ 684	