

SAE J1128 TXL
Automotive Primary Wire
125°C

Features

Conductors available in tinned or copper
 Insulation: 125°C XLPE
 RoHS and REACH Compliant

Product Design Options

Custom strand constructions
 Custom diameter to meet design criteria
 Various colors for base and stripe combinations
 Packaging options: reels or drums

Compliances

Ford ESB-M1L123-A
 Ford ESB-M1I123-A2
 Chrysler MS-8288

Applications

Cables used for automotive electrical

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Min Avg Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
22	7	30	0.030	0.062	0.013	4	2
20	7	28	0.038	0.070	0.013	5	3
18	16	30	0.048	0.082	0.013	7	5
18	19	31	0.045	0.078	0.013	7	5
16	19	29	0.056	0.088	0.013	10	7
14	19	27	0.069	0.103	0.013	15	12
12	19	25	0.088	0.128	0.015	23	18
10	19	23	0.108	0.155	0.017	37	30
8	19	21	0.137	0.191	0.018	57	48

www.lapptannehill.com • sales@lapptannehill.com
 800.633.6339