

UL 1429/1534



Construction: **Conductors:** Solid or stranded tinned or bare copper. **Insulation:** XLPVC. **Jacket:** PVC.



This hook-up wire is 150V rated and will not melt in soldering applications. It has excellent mechanical properties and is resistant to fluids.

Features:

- Good high temperature performance
- High mechanical strength
- Excellent for wiring electronic equipment
- 150V rated

Technical Data:

Temperature: 80°C

Rated Voltage:
UL 1429: 150V
UL 1534: No voltage rating

Color Code: Replace the X
0-Black, 1-Brown, 2-Red,
3-Orange, 4-Yellow, 5-Green,
6-Blue, 7-Violet, 8-Gray, 9-White,
54-Green/Yellow

Approvals:
UL 1429 + 1524 VW-1
CSA AWM, FT 1

Part Number	AWG	Stranding	Insulation Wall Inches	Nominal Outer Diameter Inches
UL 1429				
1429-26-1-X	26	1/24	.011	.038
1429-26-7-X	26	7/ 34	.011	.040
1429-26-19-X	26	19/38	.011	.041
1429-24-1-X	24	1/22	.011	.042
1429-24-7-X	24	7/32	.011	.044
1429-24-19-X	24	19/36	.011	.045
1429-22-1-X	24	1/22	.011	.047
1429-22-7-X	22	7/30	.011	.051
1429-22-19-X	22	19/34	.011	.053
1429-20-1-X	20	1/20	.011	.054
1429-20-7-X	20	7/28	.011	.059
1429-20-19-X	20	19/32	.011	.061
1429-18-1-X	18	1/26	.011	.062
1429-18-7-X	18	7/26	.011	.069
1429-18-19-X	18	19/30	.011	.070
1429-16-19-X	16	19/.0117	.012	.080
UL 1534				
1534-14-19-X	14	19/.0186	.012	.095

Not finding what you are looking for?
Please contact us at sales@lapptannehill.com, or visit our website at: www.lapptannehill.com