

Cross Link Lead Wire

UL 1430 & 3317



Construction: **Conductors:** Solid or stranded tinned or bare copper. **Insulation:** XLPVC.



This hook-up wire is 300V rated and will not melt in soldering applications. It has excellent mechanical properties and is resistant to fluids.

Features:

- Good high temperature performance
- High mechanical strength
- Excellent for wiring electronic equipment
- 300V rated

Technical Data:

Temperature: 105°C

Rated Voltage:
UL 1430: 300V
UL 3317: 300V

Color Code: Replace the X
0-Black, 1-Brown, 2-Red,
3-Orange, 4-Yellow, 5-Green,
6-Blue, 7-Violet, 8-Gray, 9-White,
54-Green/Yellow

Approvals:
UL 1430 + 3317
CSA Type RR64 (90°C)
CSA Type REW (105°C)

UL1430

UL3317

Part Number	AWG	Stranding	Insulation Thickness (mils)	Nominal Outer Diameter Inches	Part Number	AWG	Stranding	Insulation Thickness (mils)	Nominal Outer Diameter Inches
1430-28-7-X	28	7X36	0.049	1.245	3317-14-1-X	14	Solid	0.098	2.489
1430-26-1-X	26	Solid	0.05	1.27	3317-14-19-X	14	19x.0147	0.107	2.718
1430-26-7-X	26	7x34	0.051	1.295	3317-14-41-X	14	41x30	0.109	2.769
1430-26-19-X	26	19x38	0.053	1.345	3317-12-1-X	12	Solid	0.115	2.921
1430-24-1-X	24	Solid	0.054	1.372	3317-12-19-X	12	19x.0185	0.124	3.15
1430-24-7-X	24	7x32	0.056	1.422	3317-12-65-X	12	65x30	0.127	3.226
1430-24-19-X	24	19x36	0.057	1.448	3317-10-37-X	10	37x.0167	0.149	3.785
1430-22-1-X	22	Solid	0.059	1.499	3317-10-105-X	10	105x30	0.156	3.962
1430-22-7-X	22	7x30	0.062	1.575					
1430-22-19-X	22	19x34	0.063	1.6					
1430-20-1-X	20	Solid	0.066	1.676					
1430-20-7-X	20	7x28	0.07	1.778					
1430-20-19-X	20	19x32	0.071	1.803					
1430-20-10-X	20	10x30	0.071	1.803					
1430-18-1-X	18	Solid	0.074	1.88					
1430-18-7-X	18	7x26	0.082	2.083					
1430-18-19-X	18	19x30	0.082	2.083					
1430-18-16-X	18	16x30	0.082	2.086					
1430-16-1-X	16	Solid	0.085	2.159					
1430-16-19-X	16	19x.0117	0.092	2.337					
1430-16-26-X	16	26x30	0.092	2.337					

Please contact your sales representative for detailed information at sales@lapptannehill.com