

Cross Link Lead Wire

UL 3265

Construction: **Conductors:** Tin-coated copper. **Insulation:** Flame retardant cross-linked polyethelene. **Jacket:** PVC.



UL 3265 hook-up wire has a highly flame retardant XLPE insulation. It is rated for 150V and 125°C and is ideal for process controls, panel wiring & appliances.

Part Number	AWG	Stranding	Nominal Inches	Nominal Outer Diameter mm
3265-30-7-X	30	7X38	0.032	0.81
3265-28-7-X	28	7X36	0.035	0.89
3265-26-7-X	26	7X34	0.039	0.99
3265-26-19-X	26	19X38	.040	1.02
3265-24-7-X	24	7X32	0.044	1.12
3265-24-19-X	24	19X36	.045	1.14
3265-22-7-X	22	7X30	.050	1.27
3265-22-19-X	22	19X34	.052	1.32
3265-20-7-X	20	7X28	.058	1.47
3265-20-19-X	20	19X32	.060	1.52
3265-18-7-X	18	7X26	.068	1.73
3265-18-16-X	18	16X30	.068	1.73
3265-18-19-X	18	19X30	.070	1.78
3265-16-19-X	16	19X.0117	.077	1.96
3265-16-26-X	16	26X30	.080	2.03

Features:

- Excellent flame protection
- High temperature performance
- Excellent electrical properties
- Flexible copper stranding

Technical Data:

Temperature: 125°C

Rated Voltage: 150V

Color Code: Replace the X
0-Black, 1-Brown, 2-Red, 3-Orange,
4-Yellow, 5-Green, 6-Blue, 7-Violet,
8-Gray, 9-White, 54-Green/Yellow

Approvals:
UL 3265
CSA Type AWM

UL 3266

Construction: **Conductors:** Tin-coated copper. **Insulation:** Flame retardant cross-linked polyethelene. **Jacket:** PVC.



UL 3266 hook-up wire has a highly flame retardant XLPE insulation and is rated for 300V and 125°C. It is ideal for use as a motor lead, coil lead, panel and appliance wiring.

Part Number	AWG	Stranding	Insulation Inches	Nominal Outer Diameter mm
3266-26-7-X	26	7X34	0.051	1.29
3266-26-19-X	26	19X38	0.052	1.32
3266-24-7-X	24	7X32	0.056	1.42
3266-24-19-X	24	19X36	0.057	1.45
3266-22-7-X	22	7X30	0.062	1.58
3266-22-19-X	22	19X34	0.064	1.63
3266-20-7-X	20	7X28	0.07	1.78
3266-20-19-X	20	19X32	0.072	1.83
3266-18-7-X	18	7X26	0.08	2.03
3266-18-16-X	18	16X30	0.08	2.03
3266-18-19-X	18	19X30	0.082	2.08
3266-16-19-X	16	19X.0117	0.089	2.26
3266-16-26-X	16	26X30	0.092	2.34
3266-14-19-X	14	19X.0147	0.106	2.69
3266-14-41-X	14	41X30	0.107	2.72
3266-12-19-X	12	19X.0185	0.127	3.23
3266-12-65-X	12	65X30	0.127	3.23
3266-10-37-X	10	37X.0167	0.151	3.84
3266-10-105-X	10	105X30	0.154	3.91

Features:

- Excellent flame protection
- High temperature performance
- Excellent electrical properties
- Flexible copper stranding

Technical Data:

Temperature: 125°C

Rated Voltage: 300V

Color Code: Replace the X
0-Black, 1-Brown, 2-Red, 3-Orange,
4-Yellow, 5-Green, 6-Blue, 7-Violet,
8-Gray, 9-White, 54-Green/Yellow

Approvals:
UL 3266
CSA Type CL 1252
CSA Type AWM